



# TECHNICAL DATA SHEET

## COMPOSITE PI/PTFE INSULATED WIRE AS PER SAE AS 22759

### AS PER SAE AS 22759/80D

| Part No.      | Wire Size (AWG) | Conductor                  |               |       | Finished Wire              |               |       |                     |
|---------------|-----------------|----------------------------|---------------|-------|----------------------------|---------------|-------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |       | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |       | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.  |                            | Min.          | Max.  |                     |
| GK759/80-26-X | 26              | 19x38                      | 0.445         | 0.518 | 135.46                     | 0.762         | 0.864 | 2.161               |
| GK759/80-24-X | 24              | 19x36                      | 0.572         | 0.620 | 85.94                      | 0.864         | 0.965 | 2.980               |
| GK759/80-22-X | 22              | 19x34                      | 0.724         | 0.798 | 53.14                      | 1.016         | 1.092 | 4.396               |
| GK759/80-20-X | 20              | 19x32                      | 0.927         | 1.001 | 32.41                      | 1.219         | 1.295 | 6.631               |
| GK759/80-18-X | 18              | 19x30                      | 1.156         | 1.255 | 20.43                      | 1.422         | 1.524 | 9.909               |
| GK759/80-16-X | 16              | 19x29                      | 1.308         | 1.407 | 15.78                      | 1.600         | 1.702 | 12.442              |
| GK759/80-14-X | 14              | 19x27                      | 1.638         | 1.763 | 10.04                      | 1.930         | 2.032 | 19.072              |
| GK759/80-12-X | 12              | 37x28                      | 2.121         | 2.271 | 6.63                       | 2.438         | 2.540 | 30.247              |
| GK759/80-10-X | 10              | 37x26                      | 2.692         | 2.845 | 4.13                       | 3.023         | 3.124 | 46.786              |

'X' Shall be replaced by color code designator.

### As per SAE AS 22759/81D

| Part No.      | Wire Size (AWG) | Conductor                  |               |       | Finished Wire              |               |       |                     |
|---------------|-----------------|----------------------------|---------------|-------|----------------------------|---------------|-------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |       | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |       | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.  |                            | Min.          | Max.  |                     |
| GK759/81-26-X | 26              | 19x38                      | 0.445         | 0.518 | 184.99                     | 0.762         | 0.864 | 2.175               |
| GK759/81-24-X | 24              | 19x36                      | 0.572         | 0.620 | 93.15                      | 0.864         | 0.965 | 2.965               |
| GK759/81-22-X | 22              | 19x34                      | 0.724         | 0.798 | 57.40                      | 1.016         | 1.092 | 4.396               |
| GK759/81-20-X | 20              | 19x32                      | 0.927         | 1.003 | 35.10                      | 1.219         | 1.295 | 6.616               |

'X' Shall be replaced by color code designator.

### As per SAE AS 22759/82D

| Part No.      | Wire Size (AWG) | Conductor                  |               |       | Finished Wire              |               |       |                     |
|---------------|-----------------|----------------------------|---------------|-------|----------------------------|---------------|-------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |       | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |       | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.  |                            | Min.          | Max.  |                     |
| GK759/82-26-X | 26              | 19x38                      | 0.445         | 0.518 | 191.55                     | 0.762         | 0.864 | 2.161               |
| GK759/82-24-X | 24              | 19x36                      | 0.572         | 0.645 | 98.73                      | 0.864         | 0.965 | 2.980               |
| GK759/82-22-X | 22              | 19x34                      | 0.724         | 0.798 | 61.01                      | 1.016         | 1.092 | 4.396               |
| GK759/82-20-X | 20              | 19x32                      | 0.927         | 1.026 | 37.39                      | 1.219         | 1.295 | 6.631               |

'X' Shall be replaced by color code designator.

We are just a call away to answer all your queries!

**G.K. ENTERPRISES PRIVATE LIMITED**

C-6, Sector-65, Noida | C-7, Sector-58, Noida

Email: [contact@gkayindia.com](mailto:contact@gkayindia.com) | Website: [www.gkayindia.com](http://www.gkayindia.com) | Call: +91 9810087230, +91 9810353646



# TECHNICAL DATA SHEET

**As per SAE AS 22759/83E**

| Part No.      | Wire Size (AWG) | Conductor                  |               |        | Finished Wire              |               |        |                     |
|---------------|-----------------|----------------------------|---------------|--------|----------------------------|---------------|--------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |        | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |        | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.   |                            | Min.          | Max.   |                     |
| GK759/83-8-X  | 8               | 133x29                     | 4.013         | 4.216  | 2.16                       | 4.877         | 5.410  | 94.168              |
| GK759/83-6-X  | 6               | 133x27                     | 5.029         | 5.283  | 1.37                       | 5.867         | 6.452  | 144.232             |
| GK759/83-4-X  | 4               | 133x25                     | 6.350         | 6.680  | 0.87                       | 7.315         | 7.950  | 226.480             |
| GK759/83-2-X  | 2               | 665x30                     | 8.128         | 8.636  | 0.56                       | 9.042         | 9.881  | 354.620             |
| GK759/83-1-X  | 1               | 817x30                     | 9.144         | 9.652  | 0.46                       | 10.160        | 10.998 | 426.140             |
| GK759/83-01-X | 0               | 1045x30                    | 10.033        | 10.795 | 0.35                       | 10.973        | 12.065 | 543.850             |
| GK759/83-02-X | 00              | 1330x30                    | 11.176        | 12.065 | 0.28                       | 12.370        | 13.462 | 688.380             |
| GK759/83-03-X | 000             | 1665x30                    | 12.700        | 13.716 | 0.22                       | 13.767        | 14.859 | 847.810             |
| GK759/83-04-X | 0000            | 2109x30                    | 14.351        | 15.367 | 0.18                       | 15.291        | 16.637 | 1037.040            |

'X' Shall be replaced by color code designator.

**As per SAE AS 22759/84E**

| Part No.      | Wire Size (AWG) | Conductor                  |               |        | Finished Wire              |               |        |                     |
|---------------|-----------------|----------------------------|---------------|--------|----------------------------|---------------|--------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |        | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |        | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.   |                            | Min.          | Max.   |                     |
| GK759/84-8-X  | 8               | 133x29                     | 4.013         | 4.29   | 2.28                       | 4.88          | 5.410  | 95.062              |
| GK759/84-6-X  | 6               | 133x27                     | 5.029         | 5.38   | 1.43                       | 5.87          | 6.452  | 142.891             |
| GK759/84-4-X  | 4               | 133x25                     | 6.350         | 6.81   | 0.90                       | 7.32          | 7.950  | 230.950             |
| GK759/84-2-X  | 2               | 665x30                     | 8.128         | 8.64   | 0.47                       | 9.04          | 10.998 | 354.620             |
| GK759/84-1-X  | 1               | 817x30                     | 9.144         | 9.65   | 0.58                       | 10.160        | 12.065 | 430.610             |
| GK759/84-01-X | 0               | 1045x30                    | 10.033        | 10.795 | 0.37                       | 10.973        | 13.462 | 548.320             |
| GK759/84-02-X | 00              | 1330x30                    | 11.176        | 12.065 | 0.29                       | 12.370        | 14.859 | 688.380             |
| GK759/84-03-X | 000             | 1665x30                    | 12.700        | 13.716 | 0.23                       | 13.767        | 14.834 | 855.260             |
| GK759/84-04-X | 0000            | 2109x30                    | 14.351        | 15.367 | 0.18                       | 15.291        | 16.637 | 1084.720            |

'X' Shall be replaced by color code designator.

**As per SAE AS 22759/85E**

| Part No.      | Wire Size (AWG) | Conductor                  |               |        | Finished Wire              |               |        |                     |
|---------------|-----------------|----------------------------|---------------|--------|----------------------------|---------------|--------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |        | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |        | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.   |                            | Min.          | Max.   |                     |
| GK759/85-8-X  | 8               | 133x29                     | 4.013         | 4.293  | 2.30                       | 4.88          | 5.410  | 94.168              |
| GK759/85-6-X  | 6               | 133x27                     | 5.029         | 5.385  | 1.46                       | 5.87          | 6.452  | 144.232             |
| GK759/85-4-X  | 4               | 133x25                     | 6.350         | 6.807  | 0.92                       | 7.32          | 7.950  | 226.480             |
| GK759/85-2-X  | 2               | 665x30                     | 8.128         | 8.636  | 0.60                       | 9.042         | 9.8806 | 354.620             |
| GK759/85-1-X  | 1               | 817x30                     | 9.144         | 9.652  | 0.49                       | 10.16         | 10.998 | 426.140             |
| GK759/85-01-X | 0               | 1045x30                    | 10.033        | 10.795 | 0.38                       | 10.973        | 12.065 | 543.850             |
| GK759/85-02-X | 00              | 1330x30                    | 11.176        | 12.065 | 0.30                       | 12.370        | 13.462 | 688.380             |
| GK759/85-03-X | 000             | 1665x30                    | 12.700        | 13.716 | 0.23                       | 13.767        | 14.859 | 847.810             |
| GK759/85-04-X | 0000            | 2109x30                    | 14.351        | 15.367 | 0.18                       | 15.291        | 16.637 | 1037.040            |

'X' Shall be replaced by color code designator.

We are just a call away to answer all your queries!

**G.K. ENTERPRISES PRIVATE LIMITED**

C-6, Sector-65, Noida | C-7, Sector-58, Noida

Email: [contact@gkayindia.com](mailto:contact@gkayindia.com) | Website: [www.gkayindia.com](http://www.gkayindia.com) | Call: +91 9810087230, +91 9810353646



# TECHNICAL DATA SHEET

**As per SAE AS 22759/86E**

| Part No.      | Wire Size (AWG) | Conductor                  |               |        | Finished Wire              |               |        |                     |
|---------------|-----------------|----------------------------|---------------|--------|----------------------------|---------------|--------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |        | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |        | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.   |                            | Min.          | Max.   |                     |
| GK759/86-26-X | 26              | 19x38                      | 0.445         | 0.493  | 125.95                     | 0.838         | 0.940  | 2.310               |
| GK759/86-24-X | 24              | 19x36                      | 0.572         | 0.620  | 79.70                      | 0.965         | 1.067  | 3.278               |
| GK759/86-22-X | 22              | 19x34                      | 0.724         | 0.772  | 49.53                      | 1.092         | 1.194  | 4.619               |
| GK759/86-20-X | 20              | 19x32                      | 0.927         | 0.975  | 30.14                      | 1.295         | 1.397  | 7.003               |
| GK759/86-18-X | 18              | 19x30                      | 1.156         | 1.229  | 18.99                      | 1.549         | 1.651  | 10.281              |
| GK759/86-16-X | 16              | 19x29                      | 1.308         | 1.382  | 14.83                      | 1.727         | 1.854  | 13.112              |
| GK759/86-14-X | 14              | 19x27                      | 1.638         | 1.737  | 9.45                       | 2.057         | 2.184  | 19.966              |
| GK759/86-12-X | 12              | 37x28                      | 2.121         | 2.220  | 6.23                       | 2.540         | 2.667  | 30.396              |
| GK759/86-10-X | 10              | 37x26                      | 2.692         | 2.794  | 3.90                       | 3.099         | 3.226  | 47.084              |
| GK759/86-8-X  | 8               | 133x29                     | 4.013         | 4.216  | 2.16                       | 4.572         | 4.775  | 88.953              |
| GK759/86-6-X  | 6               | 133x27                     | 5.029         | 5.283  | 1.37                       | 5.563         | 5.817  | 136.931             |
| GK759/86-4-X  | 4               | 133x25                     | 6.350         | 6.680  | 0.87                       | 7.010         | 7.315  | 222.010             |
| GK759/86-2-X  | 2               | 665x30                     | 8.128         | 8.636  | 0.56                       | 8.738         | 9.246  | 347.170             |
| GK759/86-1-X  | 1               | 817x30                     | 9.144         | 9.652  | 0.46                       | 9.855         | 10.363 | 421.670             |
| GK759/86-01-X | 0               | 1045x30                    | 10.033        | 10.795 | 0.35                       | 10.668        | 11.430 | 540.870             |
| GK759/86-02-X | 00              | 1330x30                    | 11.176        | 12.065 | 0.28                       | 12.065        | 12.827 | 680.930             |
| GK759/86-03-X | 000             | 1665x30                    | 12.700        | 13.716 | 0.22                       | 13.462        | 14.224 | 846.320             |
| GK759/86-04-X | 0000            | 2109x30                    | 14.351        | 15.367 | 0.18                       | 14.986        | 16.002 | 1072.800            |

'X' Shall be replaced by color code designator.

**As per SAE AS 22759/87E**

| Part No.      | Wire Size (AWG) | Conductor                  |               |        | Finished Wire              |               |        |                     |
|---------------|-----------------|----------------------------|---------------|--------|----------------------------|---------------|--------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |        | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |        | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.   |                            | Min.          | Max.   |                     |
| GK759/87-26-X | 26              | 19x38                      | 0.445         | 0.518  | 138.42                     | 0.838         | 0.940  | 2.310               |
| GK759/87-24-X | 24              | 19x36                      | 0.572         | 0.620  | 84.95                      | 0.965         | 1.067  | 3.278               |
| GK759/87-22-X | 22              | 19x34                      | 0.724         | 0.798  | 52.48                      | 1.092         | 1.194  | 4.619               |
| GK759/87-20-X | 20              | 19x32                      | 0.927         | 1.001  | 32.05                      | 1.295         | 1.397  | 6.929               |
| GK759/87-18-X | 18              | 19x30                      | 1.156         | 1.255  | 20.01                      | 1.549         | 1.651  | 10.207              |
| GK759/87-16-X | 16              | 19x29                      | 1.308         | 1.407  | 15.61                      | 1.727         | 1.854  | 12.963              |
| GK759/87-14-X | 14              | 19x27                      | 1.638         | 1.763  | 9.84                       | 2.057         | 2.184  | 19.817              |
| GK759/87-12-X | 12              | 37x28                      | 2.121         | 2.271  | 6.49                       | 2.540         | 2.667  | 30.098              |
| GK759/87-10-X | 10              | 37x26                      | 2.692         | 2.845  | 4.07                       | 3.099         | 3.226  | 47.084              |
| GK759/87-8-X  | 8               | 133x29                     | 4.013         | 4.293  | 2.28                       | 4.572         | 4.775  | 88.953              |
| GK759/87-6-X  | 6               | 133x27                     | 5.029         | 5.385  | 1.43                       | 5.563         | 5.817  | 136.931             |
| GK759/87-4-X  | 4               | 133x25                     | 6.350         | 6.807  | 0.90                       | 7.010         | 7.315  | 222.010             |
| GK759/87-2-X  | 2               | 665x30                     | 8.128         | 8.636  | 0.58                       | 8.738         | 9.246  | 347.170             |
| GK759/87-1-X  | 1               | 817x30                     | 9.144         | 9.652  | 0.47                       | 9.855         | 10.363 | 421.670             |
| GK759/87-01-X | 0               | 1045x30                    | 10.033        | 10.795 | 0.37                       | 10.668        | 11.430 | 540.870             |
| GK759/87-02-X | 00              | 1330x30                    | 11.176        | 12.065 | 0.29                       | 12.065        | 12.827 | 680.930             |
| GK759/87-03-X | 000             | 1665x30                    | 12.700        | 13.716 | 0.23                       | 13.462        | 14.224 | 846.320             |
| GK759/87-04-X | 0000            | 2109x30                    | 14.351        | 15.367 | 0.18                       | 14.986        | 16.002 | 1072.800            |

'X' Shall be replaced by color code designator.

We are just a call away to answer all your queries!

**G.K. ENTERPRISES PRIVATE LIMITED**

C-6, Sector-65, Noida | C-7, Sector-58, Noida

Email: [contact@gkayindia.com](mailto:contact@gkayindia.com) | Website: [www.gkayindia.com](http://www.gkayindia.com) | Call: +91 9810087230, +91 9810353646



# TECHNICAL DATA SHEET

**As per SAE AS 22759/88E**

| Part No.      | Wire Size (AWG) | Conductor                  |               |        | Finished Wire              |               |        |                     |
|---------------|-----------------|----------------------------|---------------|--------|----------------------------|---------------|--------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |        | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |        | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.   |                            | Min.          | Max.   |                     |
| GK759/88-26-X | 26              | 19x38                      | 0.445         | 0.518  | 135.46                     | 0.838         | 0.940  | 2.310               |
| GK759/88-24-X | 24              | 19x36                      | 0.572         | 0.620  | 85.94                      | 0.965         | 1.067  | 3.278               |
| GK759/88-22-X | 22              | 19x34                      | 0.724         | 0.798  | 53.14                      | 1.092         | 1.194  | 4.619               |
| GK759/88-20-X | 20              | 19x32                      | 0.927         | 1.001  | 32.41                      | 1.295         | 1.397  | 6.929               |
| GK759/88-18-X | 18              | 19x30                      | 1.156         | 1.255  | 20.43                      | 1.549         | 1.651  | 10.207              |
| GK759/88-16-X | 16              | 19x29                      | 1.308         | 1.407  | 15.78                      | 1.727         | 1.854  | 12.963              |
| GK759/88-14-X | 14              | 19x27                      | 1.638         | 1.763  | 10.04                      | 2.057         | 2.184  | 19.817              |
| GK759/88-12-X | 12              | 37x28                      | 2.121         | 2.271  | 6.63                       | 2.540         | 2.667  | 30.098              |
| GK759/88-10-X | 10              | 37x26                      | 2.692         | 2.845  | 4.13                       | 3.099         | 3.226  | 47.978              |
| GK759/88-8-X  | 8               | 133x29                     | 4.013         | 4.293  | 2.30                       | 4.572         | 4.775  | 88.953              |
| GK759/88-6-X  | 6               | 133x27                     | 5.029         | 5.385  | 1.46                       | 5.563         | 5.817  | 136.931             |
| GK759/88-4-X  | 4               | 133x25                     | 6.350         | 6.807  | 0.92                       | 7.010         | 7.315  | 222.010             |
| GK759/88-2-X  | 2               | 665x30                     | 8.128         | 8.636  | 0.60                       | 8.738         | 9.246  | 347.170             |
| GK759/88-1-X  | 1               | 817x30                     | 9.144         | 9.652  | 0.49                       | 9.855         | 10.363 | 421.670             |
| GK759/88-01-X | 0               | 1045x30                    | 10.033        | 10.795 | 0.38                       | 10.668        | 11.430 | 540.870             |
| GK759/88-02-X | 00              | 1330x30                    | 11.176        | 12.065 | 0.30                       | 12.065        | 12.827 | 680.930             |
| GK759/88-03-X | 000             | 1665x30                    | 12.700        | 13.716 | 0.23                       | 13.462        | 14.224 | 846.320             |
| GK759/88-04-X | 0000            | 2109x30                    | 14.351        | 15.367 | 0.18                       | 14.986        | 16.002 | 1072.800            |

'X' Shall be replaced by color code designator.

**As per SAE AS 22759/89E**

| Part No.      | Wire Size (AWG) | Conductor                  |               |       | Finished Wire              |               |       |                     |
|---------------|-----------------|----------------------------|---------------|-------|----------------------------|---------------|-------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |       | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |       | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.  |                            | Min.          | Max.  |                     |
| GK759/89-26-X | 26              | 19x38                      | 0.445         | 0.518 | 184.99                     | 0.838         | 0.940 | 2.384               |
| GK759/89-24-X | 24              | 19x36                      | 0.572         | 0.620 | 93.15                      | 0.965         | 1.067 | 3.278               |
| GK759/89-22-X | 22              | 19x34                      | 0.724         | 0.798 | 57.40                      | 1.092         | 1.194 | 4.619               |
| GK759/89-20-X | 20              | 19x32                      | 0.927         | 1.003 | 35.10                      | 1.295         | 1.397 | 7.003               |

'X' Shall be replaced by color code designator.

**As per SAE AS 22759/90D**

| Part No.      | Wire Size (AWG) | Conductor                  |               |       | Finished Wire              |               |       |                     |
|---------------|-----------------|----------------------------|---------------|-------|----------------------------|---------------|-------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |       | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |       | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.  |                            | Min.          | Max.  |                     |
| GK759/90-26-X | 26              | 19x38                      | 0.445         | 0.518 | 191.55                     | 0.838         | 0.940 | 2.384               |
| GK759/90-24-X | 24              | 19x36                      | 0.572         | 0.645 | 98.73                      | 0.965         | 1.067 | 3.278               |
| GK759/90-22-X | 22              | 19x34                      | 0.724         | 0.798 | 61.01                      | 1.092         | 1.194 | 4.619               |
| GK759/90-20-X | 20              | 19x32                      | 0.927         | 1.026 | 37.39                      | 1.295         | 1.397 | 6.929               |

'X' Shall be replaced by color code designator.

We are just a call away to answer all your queries!

**G.K. ENTERPRISES PRIVATE LIMITED**

C-6, Sector-65, Noida | C-7, Sector-58, Noida

Email: [contact@gkayindia.com](mailto:contact@gkayindia.com) | Website: [www.gkayindia.com](http://www.gkayindia.com) | Call: +91 9810087230, +91 9810353646



# TECHNICAL DATA SHEET

## As per SAE AS 22759/91D

| Part No.      | Wire Size (AWG) | Conductor                  |               |       | Finished Wire              |               |       |                     |
|---------------|-----------------|----------------------------|---------------|-------|----------------------------|---------------|-------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |       | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |       | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.  |                            | Min.          | Max.  |                     |
| GK759/91-26-X | 26              | 19x38                      | 0.445         | 0.493 | 125.95                     | 0.762         | 0.864 | 2.161               |
| GK759/91-24-X | 24              | 19x36                      | 0.572         | 0.620 | 79.70                      | 0.864         | 0.965 | 2.980               |
| GK759/91-22-X | 22              | 19x34                      | 0.724         | 0.772 | 49.53                      | 1.016         | 1.092 | 4.410               |
| GK759/91-20-X | 20              | 19x32                      | 0.927         | 0.975 | 30.14                      | 1.219         | 1.295 | 6.705               |
| GK759/91-18-X | 18              | 19x30                      | 1.156         | 1.229 | 18.99                      | 1.422         | 1.524 | 9.983               |
| GK759/91-16-X | 16              | 19x29                      | 1.308         | 1.382 | 14.83                      | 1.600         | 1.702 | 12.516              |
| GK759/91-14-X | 14              | 19x27                      | 1.638         | 1.737 | 9.45                       | 1.930         | 2.032 | 19.221              |
| GK759/91-12-X | 12              | 37x28                      | 2.121         | 2.220 | 6.23                       | 2.438         | 2.540 | 29.651              |
| GK759/91-10-X | 10              | 37x26                      | 2.692         | 2.794 | 3.90                       | 3.023         | 3.124 | 45.892              |

'X' Shall be replaced by color code designator.

## As per SAE AS 22759/92D

| Part No.      | Wire Size (AWG) | Conductor                  |               |       | Finished Wire              |               |       |                     |
|---------------|-----------------|----------------------------|---------------|-------|----------------------------|---------------|-------|---------------------|
|               |                 | Stranding (N x strand AWG) | Diameter (mm) |       | Max. Resis. at 20°C (Ω/Km) | Diameter (mm) |       | Max. Weight (kg/km) |
|               |                 |                            | Min.          | Max.  |                            | Min.          | Max.  |                     |
| GK759/92-26-X | 26              | 19x38                      | 0.445         | 0.518 | 138.42                     | 0.762         | 0.864 | 2.161               |
| GK759/92-24-X | 24              | 19x36                      | 0.572         | 0.620 | 84.95                      | 0.864         | 0.965 | 2.980               |
| GK759/92-22-X | 22              | 19x34                      | 0.724         | 0.798 | 52.48                      | 1.016         | 1.092 | 4.396               |
| GK759/92-20-X | 20              | 19x32                      | 0.927         | 1.001 | 32.05                      | 1.219         | 1.295 | 6.631               |
| GK759/92-18-X | 18              | 19x30                      | 1.156         | 1.255 | 20.01                      | 1.422         | 1.524 | 9.909               |
| GK759/92-16-X | 16              | 19x29                      | 1.308         | 1.407 | 15.61                      | 1.600         | 1.702 | 12.442              |
| GK759/92-14-X | 14              | 19x27                      | 1.638         | 1.763 | 9.84                       | 1.930         | 2.032 | 19.072              |
| GK759/92-12-X | 12              | 37x28                      | 2.121         | 2.271 | 6.49                       | 2.438         | 2.540 | 29.353              |
| GK759/92-10-X | 10              | 37x26                      | 2.692         | 2.845 | 4.07                       | 3.023         | 3.124 | 45.892              |

'X' Shall be replaced by color code designator.

We are just a call away to answer all your queries!

**G.K. ENTERPRISES PRIVATE LIMITED**

C-6, Sector-65, Noida | C-7, Sector-58, Noida

Email: [contact@gkayindia.com](mailto:contact@gkayindia.com) | Website: [www.gkayindia.com](http://www.gkayindia.com) | Call: +91 9810087230, +91 9810353646