



TECHNICAL DATA SHEET

RTD CABLE FOR PT100 SENSORS

PRODUCT RANGE

Part No.	Cable Description	Cross Section Area	Conductor Stranding	Outer Dia (mm)
H4C2407	4CXA WG 24	0.22 sq mm	7 x 0.2 mm	2.9
H6C2407	6CXA WG 24	0.22 sq mm	7 x 0.2 mm	3.9
H3C2007	3CXA WG 20	0.50 sq mm	7 x 0.32 mm	3.6
H4C2007	4CXA WG 20	0.50 sq mm	7 x 0.32 mm	3.9
H6C2007	6CXA WG 20	0.50 sq mm	7 x 0.32 mm	4.8

In case of SS over braiding, add 'S' in cable part no., e.g. "H3C2407S"

Part No.	Cable Description	Cross Section Area	Conductor Stranding	Outer Dia (mm)
P4C2007	4CXA WG 20	0.5 sq mm	7 x 0.32 mm	5.7
P6C2007	6CXA WG 20	0.5 sq mm	7 x 0.32 mm	6.9
P3C1814	3CXA WG 18	1.0 sq mm	14 x 0.3 mm	6.7
P4C1814	4CXA WG 18	1.0 sq mm	14 x 0.3 mm	7.3
P6C1814	6CXA WG 18	1.0 sq mm	14 x 0.3 mm	8.9

In case of shielding with Al mylar and drain wire, add 'S' in cable part no., e.g. "P3C2007S"

Part No.	Cable Description	Cross Section Area	Conductor Stranding	Outer Dia (mm)
P4C2007SA	4CXA WG 20	0.5 sq mm	7 x 0.32 mm	10.5
P6C2007SA	6CXA WG 20	0.5 sq mm	7 x 0.32 mm	11.5
P3C1814SA	3CXA WG 18	1.0 sq mm	14 x 0.3 mm	12.5
P4C1814SA	4CXA WG 18	1.0 sq mm	14 x 0.3 mm	13.2
P6C1814SA	6CXA WG 18	1.0 sq mm	14 x 0.3 mm	14.7

We are just a call away to answer all your queries!

G.K. ENTERPRISES PRIVATE LIMITED

C-6, Sector-65, Noida | C-7, Sector-58, Noida

Email: contact@gkayindia.com | Website: www.gkayindia.com | Call: +91 9810087230, +91 9810353646